


Accesorio de cojinete 7610-DL-NICE - 7610-DL-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/cojinete/accesorio/7610-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE™**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE TIGHT BEARING
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE OILED
- EXCELLENT APPLICABLE SINGLE LIP CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS IS NOT STANDARD IN AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EFFICIENCY, WEIGHT AND RELIABILITY ARE REQUIRED.



BEARING Ø	PRINCIPLE DIMENSIONS				
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)
7610™	.6250 15.88	1.7500 44.50	0.6250 16.00	0.0625 1.59	1.000 25.40

PRINCIPLE DIMENSIONS					BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.062 27.74	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4961

When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear

Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) Weights given are for greased and sealed versions

All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3616060473417
Diámetro interior	15.88 mm
Diámetro interior	5/8" inch
Diámetro exterior	25.63 mm
Diámetro exterior	1.009" inch
Espesor	15.88 mm
Espesor	5/8" inch
Peso	150 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE