



Accesorio de cojinete 7614-DL-NICE - 7614-DL-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/cojinete/accesorio/7614-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 8000 - 8000 RPM
- THROUGH HOLES
- STAINLESS STEEL STANDARD
- METRIC BEARING
- QUANTITY APPROXIMATE ANGLES OF CONTACT
- AVAILABLE SINGLE BEARING OR OPEN END BEARING
- ALL BEARING MUST BE OIL-FILLED
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEAT IS NOT A FACTOR





BEARING	PRINCIPLE DIMENSIONS					
	BORE	O.D.	WIDTH			
d (in) (mm)	D (in) (mm)	B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)	
7614™	+0.008 +0.000 -0.000 -0.000	+0.000 +0.000 -0.0005 -0.013	+0.000 -0.000 -0.005	0.0625 1.58	1.308 33.17	+0.005 +13 -0.05 -13
	0.1750 22.23	2.0312 51.83	0.6250 15.88			0.136 3.45

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H	J	K	L	M	N	Radius R	Dynamic C	Static C ₀	W
(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	2 set screws	(in) (mm)	(lb) (N)	(lb) (N)	(lb) (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28	0.039 0.99	2970 13217	1350 6098	0.43 0.20

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +0.0005/-0.0005 (+0.000/-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear.
 ④ Weights given are for greased and sealed versions.
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3616060473455
Diámetro interior	22.23 mm
Diámetro exterior	33.17 mm
Espesor	15.88 mm
Peso	200 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE