


Accesorio de cojinete 7615-DL-NICE - 7615-DL-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/cojinete/accesorio/7615-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE - 5000 - 8000 RPM
- PRECISION MANUFACTURE
- STEEL BEARING
- WIPER CASE STANDARD
- STANDARD BEARING STANDARD
- SHARPLY ANGLED SINGLE LIP CONTACT SURFACES
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP END SURFACE - THIS SIDE ORIENTABLE TO AN APPLICATION
- RECOMMENDED FOR APPLICATIONS WHERE WEIGHT, SPEED, PRECISION AND EXTENDED LIFE ARE REQUIRED



| BEARING Ø | PRINCIPLE DIMENSIONS | | | | | |
|-----------|--|--|----------------------------|----------------|-------------------|-----------------------------------|
| | BORE d (in) (mm) | O.D. D (in) (mm) | WIDTH B (in) (mm) | | F (in) (mm) | G (in) (mm) |
| 7615™ Ø | +0.0008 +0.000 -0.0000 -0.000 | +0.0000 +0.000 -0.0005 Ø -0.013 | +0.000 0.000 -0.005 | 0.0625 1.59 | 1.308 33.17 | +0.005 +0.13 -0.05 -0.13 |

| PRINCIPLE DIMENSIONS | | | | | | BASIC LOAD RATINGS | | WEIGHT | |
|----------------------|-------------------|-------------------|-------------------|-------------------|--------------------------------------|--------------------------|-----------------------------|---|-------------------|
| H (in) (mm) | J (in) (mm) | K (in) (mm) | L (in) (mm) | M (in) (mm) | N 2 set screws (in) (mm) | Radius R (in) (mm) | Dynamic C (lb) (N) | Static C ₀ (lb) (N) | W (lb) (kg) |
| 0.042 1.07 | 2.158 54.77 | 1.179 29.95 | 0.492 12.50 | 0.261 6.63 | 1/4-28 | 0.039 0.99 | 2970 13217 | 1560 6998 | 0.40 0.18 |

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
② Tolerance for 7615™ and larger is +0.0000/-0.0005 (+0.000/-0.015)
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | NICE |
| Nº Ean13 | 3616060473462 |
| Diámetro interior | 23.81 mm |
| Diámetro exterior | 33.17 mm |
| Espesor | 15.88 mm |
| Peso | 180 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE