


Accesorio de cojinete ER20-NICE - ER20-NICE

<https://www.123rodamiento.es/rodamiento-cojinete/cojinete/accesorio/er20-nice>

ER Series Precision Ground Radial Bearings with **NICE**
Extended Inner Ring and Metric Outside Diameter

- EXCELLENCE, HEAVY DUTY "N1" BEARINGS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LUBRICATION GROOVES PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LIP-FORMING SEAL IS AVAILABLE
- LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO KNURLED DIP POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING OILING UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK OXIDE FINISH PROVIDES ADDITIONAL CORROSION RESISTANCE



PRINCIPLE DIMENSIONS													
BASIC BEARING NUMBER	SHAFT Ø (in) (mm)	OD (in) (mm)	WIDTH (in) (mm)	C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)	H (in) (mm)	J (in) (mm)	K (in) (mm)	M (in) (mm)	RADIUS (in) (mm)
ER20	1 5/4 31.75	2.8340 72	1 11/16 46.04	13/16 25.40	1 25.40	3/4 19.05	1 13/16 46.04	7/32 5.56	1/16 1.59	1/8 3.18	1/4 6.35	15/16 23.81	0.040 1.02

RADIAL CAPACITY										WEIGHT			
Ø (in) (mm)	P (in) (mm)	3-SET SCREWS	BASIC LOAD STATIC LOAD		REVOLUTIONS PER MINUTE						W (lbs) (kg)		
			RATING C (in) (N)	RATING Co (in) (lbs) (N)	50	150	300	500	1200	1800		2500	5000
0.219 5.56	3 5/64 23.18	1/4-20	5755 25810	3450 12353	1852 8241	1284 5714	1019 4535	859 3853	642 2897	581 2604	502 2254	399 1778	0.93 0.42

Shaft tolerance +.0002/-0.005 (+.002/-0.13) For low torque version add suffix "SFF"

CARACTERÍSTICAS DEL PRODUCTO

Marca	NICE
Nº Ean13	3663952560878
Diámetro interior	31.75 mm
Diámetro exterior	46.04 mm
Espesor	23.81 mm
Peso	420 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE