


Rotulas TSM MSX-M12-DUNLOP - MSX-M12-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tsm/msx-m12-dunlop>

MALE ROD ENDS

MALE ROD ENDS

Description:
MSX series is our 3-piece steel on steel high strength range of male rod ends designed for motorsport and heavy industrial mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the inner race, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, heat treated, zinc plated and clear trivalent passivate. Inner Ring: Steel 070M20, zinc plated and clear trivalent passivate and stainless steel 316C. Liner: High strength PTFE bronze mesh composite. Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium/heavy industrial/mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +260°C

Specification:
EN & JIS compliant

Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate	Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate	Liner: High Strength PTFE Composite
Temp Range: -200°C to +260°C	

Part No. Right Hand	Part No. Left Hand	Bore size	Thread	W	H	D	L1	L2	Static Load Rating (Newtons) Radial
MSX-M12		12	M12x1.75	16	12.00	32	54	33	42000

Interchange table

Dunlop	Aurora	Fluro
MSX MS-M (metric)	AM-M-T and AB-M-T	GAXSW
MSX MS (imperial)	AM-T and AB-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060550156
Diámetro interior	12 mm
Diámetro exterior	16 mm
Espesor	12 mm
Tipo	TSM
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE