


## Rotulas TSM MB-16-DUNLOP - MB-16-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tsm/mb-16-dunlop>

**MALE ROD ENDS**



**MB SERIES: MB - MBS - MB SS**

**Description:**  
MB Series is our 3-piece standard range of maintenance required general purpose male rod ends suitable for medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. An oil impregnated sintered bronze race is also available for some sizes or if quantity justifies production, suitable for high precision motion transfer applications and extended wear life.

**Material Specifications:**  
Housing: Steel 230M07PB and forged 083M44, zinc plated and clear trivalent passivate and stainless steel 303L 304. Forged. Race: Bronze SAE540 and oil impregnated sintered bronze. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated and stainless steel 440C. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303L.

**Features:**  
Metric & imperial thread & bore sizes  
Low friction  
Self-lubricating option available  
Extended wear life  
Maintenance required  
Studding option

**Possible Applications:**  
Medium/heavy industrial/  
mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
Precision equipment

**Temperature Range:**  
-34°C to +143°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Steel 230M07PB (Sizes 083,071, Forged 083M44 (Sizes 08 - 16), Zinc Plated and Clear Trivalent Passivate

**Race:** Bronze SAE540

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MB-16		1	1" UNF	1.375	1.00	2.750	4.125	2.125	1.486	47,500

**Interchange table**

Dunlop	Rose	Tuthill	Alinabal	SKF	Asahi	IKO	Fluro
MB-M (metric)	MM	MB-M	MM-M	SARAC-M	JAM	POS	GAS
MB (imperial)	RM-U	MB	VM-D	-	-	POSB	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

**For stainless steel add 'SS' to part no. For example 'MB-M03 SS'**

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	5059161182266
Diámetro interior	25.4 mm
Diámetro exterior	69.85 mm
Espesor	34.925 mm
Tipo	TSM
Hilo	Rosca derecha
Lubricación	NA
Carga estática	0.0475 kN
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE