



Rotulas TSM MBL-07-DUNLOP - MBL-07-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tsm/mb1-07-dunlop>

MALE ROD ENDS 



MB SERIES: MB - MBS - MB SS

Description:
MB Series is our 3-piece standard range of maintenance required general purpose male rod ends suitable for medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. An oil impregnated sintered bronze race is also available for some sizes or if quantity justifies production, suitable for high precision motion transfer applications and extended wear life.

Material Specifications:
Housing: Steel 230M07PB (Sizes 08-30T) Forged 08M44 (Sizes 36 - 54) Zinc Plated and Clear Trivalent Passivate
Race: Bronze SAE540
Balls: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Features:
Metric & imperial thread & bore sizes
Low friction
Self-lubricating option available
Extended wear life
Maintenance required
Standard option

Possible Applications:
Medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
Precision equipment

Temperature Range:
-34°C to +145°C

Specifications:
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MBL-07		7/16	7/16 UNF	0.562	0.437	1.125	2.125	1.375	0.586	16,360

Interchange table

Dunlop	Rose	Tuthill	Alinabal	SKF	Asahi	IKO	Fluro
MB-M (metric)	MM	MB-M	MM-M	SARAC-M	JAM	POS	GAS
MB (imperial)	RM-U	MB	VM-D	-	-	POSB	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.
For stainless steel add 'SS' to part no. For example 'MB-M03 SS'

CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060551047
Diámetro interior	11.0998 mm
Diámetro interior	0.437" inch
Diámetro exterior	28.575 mm
Diámetro exterior	1 1/8" inch
Espesor	14.2748 mm
Espesor	0.562" inch
Tipo	TSM
Hilo	Rosca izquierda
Lubricación	NA
Carga estática	0.0164 kN
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE