

Rotulas SI

FSL-12-10-F-DUNLOP - FSL-12-10-F-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/fsl-12-10-f-dunlop>

FEMALE ROD ENDS

DUNLOP

FS SERIES: FS - FSS - FS SS

Description:
FS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 230M07Pb (50mm Ø) and forged 60MnS, zinc plated and clear trivalent passivate and stainless steel 302L and forged 304. Inner Ring: Steel 670M020 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6, heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, extended wear life, no maintenance, slotted end stainless steel options.

Possible Applications:
Medium/heavy industrial mechanical applications, construction equipment, agricultural equipment, motor sport and recreational vehicles requiring high precision motion control.

Temperature Ranges:
-200°C to +750°C

Specification:
ELV & RoHS compliant

Housing: Steel 230M07Pb (50mm Ø) and forged 60MnS, zinc plated and clear trivalent passivate and stainless steel 302L and forged 304. Inner Ring: Steel 670M020 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite.

Part No. Right Hand | **Part No. Left Hand** | **Bore Size** | **Thread** | **W** | **H** | **D** | **L1** | **L2** | **O** | **AF** | **Static Load Rating (Newtons) Radial**

FSL-12-10F | S/B | 3/4 BSF | 0.875 | 0.687 | 2.000 | 2.875 | 1.750 | 24.80 | 1.000 | 45,000

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	Asahi	IKO	Fluro
FS-M (metric)	MFC	MW-M-T and MG-M-T	KI-P	SKB-F	JAF-EC	PHS-EC	QISW
FS (imperial)	RFC	MW-T and MG-T	-	-	PHSB-EC	-	-

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060554628
Diámetro interior	15.87 mm
Diámetro exterior	0.875 mm
Espesor	0.687 mm
Tipo	SI
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE