

Rotulas SI

FXL-12-G-DUNLOP - FXL-12-G-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/fxl-12-g-dunlop>

FEMALE ROD ENDS 



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 40, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated 80/90 tons/in² tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
FXL-12G		.7500	.875	.812	1.000	2.125	3.125	1.750	1.125	3/4 UNF	16	110810

Interchange table

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060556127
Diámetro interior	7500 mm
Diámetro interior	295.276" inch
Diámetro exterior	875 mm
Diámetro exterior	34.449" inch
Espesor	812 mm
Espesor	31.969" inch
Tipo	SI
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE