



Rotulas GE GE100-FW-DUNLOP - GE100-FW-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge100-fw-dunlop>

SPHERICAL BEARINGS

GE FW SERIES

Description:
GE-FW-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium/heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range:
-52°C to +121°C

Specification:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened **Race:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE100FW		100	85	95	160	3,075,000

CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060557391
Diámetro interior	100 mm
Diámetro exterior	160 mm
Espesor	85 mm
Tipo	GE
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE