

Rotulas GE

GE212-ES-2RS-DUNLOP - GE212-ES-2RS-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/ge212-es-2rs-dunlop>

SPHERICAL BEARINGS 



GE ES SERIES

Description:
GE2-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seats: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specification:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seats: Polyurethane

| Part No. Unsealed | Part No. Sealed | Bore Size | W | H | D | Static Load Rating (Newtons) Radial |
|-------------------|-----------------|-----------|--------|--------|---------|-------------------------------------|
| | GE212ES-2RS | 2-3/4 | 61.112 | 52.375 | 111.125 | 1,250,000 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | DUNLOP |
| Nº Ean13 | 3616060558299 |
| Diámetro interior | 19.5 mm |
| Diámetro exterior | 61.11 mm |
| Espesor | 52.37 mm |
| Tipo | GE |
| Hilo | Rosca derecha |
| Lubricación | con |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE