

# Rotulas GE

## GE17-UK-2RS-DUNLOP - GE17-UK-2RS-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/ge17-uk-2rs-dunlop>

SPHERICAL BEARINGS






**GE UK SERIES**

**Description:**  
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.  
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.  
Seals: Polyurethane.

<p><b>Features</b></p> <ul style="list-style-type: none"> <li>Metric bore sizes</li> <li>Low friction</li> <li>High shock loads</li> <li>Extended wear life</li> <li>No maintenance</li> </ul>	<p><b>Possible Applications</b></p> <ul style="list-style-type: none"> <li>Medium-heavy industrial mechanical applications</li> <li>Construction equipment</li> <li>Agricultural equipment</li> <li>Recreational vehicles</li> <li>High precision motion control</li> </ul>	<p><b>Temperature Range</b></p> <p>-200°C to +260°C</p> <p><b>Specification</b></p> <p>ELV &amp; RoHS compliant</p>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------

Outer Ring: Bearing Steel 100Cr6, Case Hardened      Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GE17UK-2RS	17	14	10	30	54,000

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060558411
Diámetro interior	17 mm
Diámetro exterior	30 mm
Espesor	14 mm
Tipo	GE
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE