


# Rotulas GE

## GE45-UK-DUNLOP - GE45-UK-DUNLOP

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/ge45-uk-dunlop>

SPHERICAL BEARINGS 





**GE UK SERIES**

**Description:**  
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.  
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.  
Seals: Polyurethane.

**Features**  
Metric bore sizes  
Low friction  
High shock loads  
Extended wear life  
No maintenance

**Possible Applications**  
Medium/heavy industrial mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control

**Temperature Range**  
-200°C to +260°C  
**Specification**  
ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened     **Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
**Liner:** High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE45UK		45	32	25	68	340,000

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DUNLOP
Nº Ean13	3616060558534
Diámetro interior	45 mm
Diámetro exterior	32 mm
Espesor	25 mm
Tipo	GE
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE