

Casquillos de agujas BA1820-Z-IKO - BA1820-Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/ba1820-z-iko>



Boundary dimensions mm[inch]		Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed	Assembled inner ring
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>d₂</i>	Shaft dia. Int	Housing bore dia. <i>d₁</i>	<i>C</i>	<i>C_d</i>	<i>C_s</i>	rpm		
28.575 (1.124)	34.925 (1.375)	31.75 (1.250)	28.575 (1.125)	28.575 (1.125)	34.925 (1.375)	25.700 (1.012)	53.900 (2.122)	13000 (RB 1420)			

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060601285
Diámetro interior	28.575 mm
Diámetro interior	1 1/8" inch
Diámetro exterior	34.925 mm
Diámetro exterior	1 3/8" inch
Espesor	31.75 mm
Espesor	1 1/4" inch
Velocidad límite	13000 rpm
Carga dinámica	25.7 kN
Carga estática	53.9 kN
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE