

## Casquillos de agujas BA1412-Z-IKO - BA1412-Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/ba1412-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic	Basic static	Allowable	Assembled	
$F_w$	$D$	$C$	$l_2$	$t_5$	$l_7$	$M_5$	$C$	$C_0$	rotational	inner ring	
			Max.	Min.	Max.	Min.	N	N	rpm		
22.225 (A 8)	28.575 (1.1 1/8)	19.05 (7/8)	2.4	22.225	23.212	28.587	28.596	12800	20400	18000	IB 1812

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060603302
Diámetro interior	22.225 mm
Diámetro exterior	28.575 mm
Espesor	19.05 mm
Velocidad límite	18000 rpm
Carga dinámica	12.8 kN
Carga estática	20.4 kN
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE