


Rodamiento conico 2559-2525-TIMKEN - 2559-2525-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/2559-2525-timken>

TYPE TS



Dimensions		Abutment and Fillet Dimensions	
e - Skew	30.163 mm 1.1879 in	R - Case Backface To Case Face Fillet	0.762 mm 0.030 in
D - Cup Outer Diameter	72.022 mm 2.8355 in	r - Cup Backface To Case Face Fillet ²	0.76 mm 0.030 in
B - Case Width	25.267 mm 0.9943 in	Aa - Cup Frontface Backing Diameter	36.46 mm 1.43 in
C - Cup Width	19.050 mm 0.7500 in	Aa - Cup Backface Backing Diameter	27.06 mm 1.06 in
T - Skewing Width	23.813 mm 0.9375 in	Da - Cup Frontface Backing Diameter	66.00 mm 2.60 in
Basic Load Ratings		Da - Cup Backface Backing Diameter	62.99 mm 2.48 in
CRG - Dynamic Radial Rating (N) million revolutions ³	4850 (2) 21 780 N	Ab - Cage Case Frontface Clearance	5.5 mm 0.21 in
CR - Dynamic Radial Rating (1 million revolutions) ³	4850 (2) 65700 N	Aa - Cage Case Backface Clearance	0.5 mm 0.02 in
CR - Static Radial Rating	11300 (2) 94400 N	a - Effective Center Location ³	0.5 mm 0.02 in
C _{app} - Dynamic Thrust Rating (N) million revolutions ³	2280 (2) 10200 N		
Factors			
K - Factor ⁴	2.54		
v - ISO Factor ⁵	0.27		
V - ISO Factor ⁵	2.19		
G1 - Heat Generation Factor (Stiller - Baswell)	23.6		
G2 - Heat Generation Factor (Stiller - Baswell)	8.6		
G3 - Geometry Factor	0.0016		

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3616060668097
Diámetro interior	30.163 mm
Diámetro exterior	72.022 mm
Espesor	23.813 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE