

## Cojinete 2 fijaciones P2BSS-40M-YTPSS-SKF - P2BSS-40M-YTPSS-SKF

<https://www.123rodamiento.es/rodamiento-cojinete/cojinete/cojinete-hierro-fundido-2-fijaciones/p2bss-40m-ytpss-skf>

| Données de calcul        |                |          |                  |
|--------------------------|----------------|----------|------------------|
| Charge dynamique de base | C              | 24.7     | kN               |
| Charge statique de base  | C <sub>0</sub> | 19       | kN               |
| Limite de fatigue        | P <sub>0</sub> | 0.8      | kN               |
| Vitesse limite           |                | 2800     | tr/min           |
| Compliance with standard |                |          | Not standardized |
| Matériau                 |                |          | Stainless steel  |
| Sealing solution         |                |          | Gutter seals     |
| Dimensions               |                |          |                  |
|                          | D              | 40       | mm               |
|                          | D <sub>2</sub> | 61.8     | mm               |
|                          | B              | 48       | mm               |
|                          | A              | 30       | mm               |
|                          | A <sub>1</sub> | 21.5     | mm               |
|                          | B <sub>1</sub> | 49.2     | mm               |
|                          | B <sub>2</sub> | 10       | mm               |
|                          | H              | 99       | mm               |
|                          | H <sub>1</sub> | 49.2     | mm               |
|                          | H <sub>2</sub> | 19       | mm               |
|                          | J              | 135.5    | mm               |
|                          | J              | max. 146 | mm               |
|                          | J              | min. 125 | mm               |
|                          | K              | 174.5    | mm               |
|                          | N              | 24.5     | mm               |
|                          | N <sub>1</sub> | 14.5     | mm               |
|                          | S <sub>1</sub> | 30.2     | mm               |
| Piéds de centrage        |                |          |                  |
|                          | G              | 12       | mm               |
|                          | G              | 0.6      | in               |

### CARACTERÍSTICAS DEL PRODUCTO

|                                  |                              |
|----------------------------------|------------------------------|
| Marca                            | SKF                          |
| Nº Ean13                         | 3616060837707                |
| Diámetro del eje                 | 40 mm                        |
| Nº de elementos de fijación      | 2                            |
| Sujeción                         | Anillo de bloqueo excéntrico |
| Distancia del centro de fijación | 135.5 mm                     |
| Material                         | ACERO INOXIDABLE             |
| Peso                             | 1990 g                       |
| Envasado                         | 1                            |
| Estándar                         | Ninguna norma                |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE