

Rodamiento conico 32203-JR-JTEKT - 32203-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32203-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾	
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.			
17	40	17.25	16	14	1	1	27.4	27.5	10 000	14 000	32203JR

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
20D	11.4	22.5	23	34.5	33	37	2	3	1	1	0.31	1.92	1.06	0.104

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952398013
Diámetro interior	17 mm
Diámetro interior	0.669" inch
Diámetro exterior	40 mm
Diámetro exterior	1.575" inch
Espesor	17.25 mm
Espesor	0.679" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE