

## Rodamiento conico 32204-XR-JTEKT - 32204-XR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32204-xr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                      |                      |                      |                |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|----------------------|----------------------|----------------------|----------------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                      |                      |                      |                |
| 20                                     | 47                 | 19.25                    | 18                   | 16                      | 33.3                 | 37.0                 | 9 100                | 12 000                               | 32204XR              |                           |                      |                      |                      |                |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors   |                      | (Refer. 1) Mass (kg) |                |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | d <sub>2a</sub> min.    | d <sub>2a</sub> max. | D <sub>1a</sub> min. | D <sub>1a</sub> max. | S <sub>1a</sub> min.                 | S <sub>1a</sub> max. |                           | r <sub>1a</sub> min. | r <sub>1a</sub> max. |                      | Y <sub>1</sub> |
| —                                      | 15.3               | 25.5                     | 25                   | 41.5                    | 35                   | 45                   | 2                    | 3                                    | 1                    | 1                         | 0.55                 | 1.10                 | 0.60                 | 0.170          |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| N° Ean13          | 3663952400396 |
| Diámetro interior | 20 mm         |
| Diámetro exterior | 47 mm         |
| Espesor           | 19.25 mm      |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE