

Rodamiento conico TRA0607-R-JTEKT - TRA0607-R-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/tra0607-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	r ₁	r ₂	C _r	C _{0r}	Grease lub.		Oil lub.			
30	72	20.75	19	16	1.5	1.5	56.9	55.6	5 900	7 900	TRA0607R			
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁
—	18.6	38.5	39	63.5	58	68	3	4.5	1.5	1.5	0.55	1.10	0.60	0.405

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952400747
Diámetro interior	30 mm
Diámetro exterior	72 mm
Espesor	20.75 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE