

Rodamiento conico T2EE040-JTEKT - T2EE040-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/t2ee040-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
40	85	33	32.5	28	114	143	4 800	6 400	T2EE040					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2EE	21.9	52	48	75	70	80	5	5	2	2	0.34	1.74	0.96	0.900

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952404899
Diámetro interior	40 mm
Diámetro exterior	85 mm
Espesor	33 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE