

Rodamiento conico T2EE060-JTEKT - T2EE060-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/t2ee060-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
60	115	40	39	33	183	242	3 400	4 600	T2EE060					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _a min.	d _a max.	D _a min.	D _a max.	S _a min.	S _a max.	r _a min.	r _a max.		Y ₁	Y ₀		
2EE	27.6	72	70	103	98	109	6	7	2	2	0.33	1.80	0.99	1.80

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952406022
Diámetro interior	60 mm
Diámetro exterior	115 mm
Espesor	40 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE