


## Rodamiento conico 30317-D-JTEKT - 30317-D-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30317-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
85	180	44.5	41	28	231	255	1 900	2 600	30317D					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>2a</sub> max.	D <sub>4a</sub> max.	D <sub>3a</sub> min.	S <sub>1a</sub> min.	S <sub>2a</sub> min.	r <sub>3a</sub> max.	r <sub>4a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	56.0	103	103	166	143	169	6	16.5	3	2.5	0.81	0.74	0.41	4.54

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250122262
Diámetro interior	85 mm
Diámetro exterior	180 mm
Espesor	44.5 mm
Envasado	1
Estándar	Ninguna norma

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE