

Rodamiento conico T2ED080-JTEKT - T2ED080-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/t2ed080-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C_r	C_{0r}	C_{10}	C_{20}	Grease lub.	Oil lub.				
80	145	46	45	38	3	2.5	266	381	2 600	3 500	T2ED080			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d_a min.	d_b max.	D_a max.	D_b min.	S_a min.	S_b min.	r_a max.	r_b max.		Y_1	Y_0		
2ED	32.7	94	92	133	125	137	7	8	2.5	2	0.32	1.88	1.03	3.20

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952409566
Diámetro interior	80 mm
Diámetro exterior	145 mm
Espesor	46 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE