

Rodamiento conico 32919-JR-JTEKT - 32919-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32919-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|-------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 95 | 130 | 23 | 23 | 18 | 104 | 186 | 2 600 | 3 500 | 32919JR | | | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{2a} min. | D _{2a} max. | S _{1a} min. | S _{1a} max. | r _{3a} min. | r _{3a} max. | | Y ₁ | Y ₀ | | |
| 29C | 23.5 | 103.5 | 102 | 121.5 | 119 | 125 | 5 | 5 | 1.5 | 1.5 | 0.36 | 1.68 | 0.92 | 0.876 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952409702 |
| Diámetro interior | 95 mm |
| Diámetro exterior | 130 mm |
| Espesor | 23 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE