

Rodamiento conico 30319-DJR-JTEKT - 30319-DJR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30319-djr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.					
95	200	49.5	45	32	319	391	1 700	2 300	30319DJR				
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors (Refer. 1)		Mass (kg)		
7GB	62.7	d _{1a} min.	d _{2a} max.	D _{1a} max.	D _{2a} min.	S _{1a} min.	S _{2a} min.	r _{1a} max.	r _{2a} max.	Y ₁	Y ₀	6.68	
		113	113	186	157	187	6	17.5	3	2.5	0.83	0.73	0.40

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250122378
Diámetro interior	95 mm
Diámetro exterior	200 mm
Espesor	49.5 mm
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE