

Rodamiento conico 30319-JTEKT - 30319-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30319-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
95	200	49.5	45	38	4	3	317	368	2 000	2 600	30319			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
—	39.8	113	118	186	172	186	5	11.5	3	2.5	0.35	1.73	0.95	6.32

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250122354
Diámetro interior	95 mm
Diámetro exterior	200 mm
Espesor	49.5 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE