

Rodamiento conico T4CB100-JTEKT - T4CB100-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/t4cb100-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|----------------------------------------|----------------------|--------------------------|------------|------------|-------------------------|------------|------------|-------------|--------------------------------------|--------------|---------------------------|-------|----------------------|------|
| d | D | T | B | C | C_r | C_{0r} | C_{90} | Grease lub. | Oil lub. | | | | | |
| 100 | 145 | 24 | 22.5 | 17.5 | 3 | 3 | 116 | 167 | 2 400 | 3 200 | T4CB100 | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d_a min. | d_a max. | D_a min. | D_a max. | S_a min. | S_a max. | r_a min. | r_a max. | | Y_1 | Y_0 | | |
| 4CB | 29.9 | 112 | 109 | 133 | 132 | 140 | 4 | 6.5 | 2.5 | 2.5 | 0.47 | 1.27 | 0.70 | 1.12 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952410500 |
| Diámetro interior | 100 mm |
| Diámetro exterior | 145 mm |
| Espesor | 24 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE