

Rodamiento conico 30321-JR-JTEKT - 30321-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30321-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|------|----|----|-------------------------|-----------------|-----------------|-----------------|-------------|--------------------------------------|---------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₁₀ | C ₉₀ | Grease lub. | Oil lub. | | |
| 105 | 225 | 53.5 | 49 | 41 | 464 | 578 | 1700 | 2300 | | | 30321JR | |

| Dimension series to ISO355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) |
|---------------------------------------|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------------|
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | r _{2a} min. | r _{2a} max. | | Y ₁ | Y ₀ | |
| 2GB | 44.1 | 123 | 132 | 211 | 193 | 209 | 7 | 12.5 | 3 | 2.5 | 0.35 | 1.74 | 0.96 | 9.73 | |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952410715 |
| Diámetro interior | 105 mm |
| Diámetro exterior | 225 mm |
| Espesor | 53.5 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE