


## Rodamiento conico 30322-JR-JTEKT - 30322-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30322-jr-jtekt>

Single-row tapered roller bearings  
metric series Koyo



| Boundary dimensions (mm)            |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                    |      |
|-------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|--------------------|------|
| d                                   | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                    |                |                    |      |
| 110                                 | 240                | 54.5                     | 50                   | 42                      | 481                  | 590                  | 1 600                | 2 100                                | 30322JR              |                           |                    |                |                    |      |
| Dimension series to ISO355 (Refer.) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer.) Mass (kg) |      |
|                                     |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                    |      |
| 20B                                 | 46.3               | 128                      | 141                  | 226                     | 206                  | 222                  | 8                    | 12.5                                 | 3                    | 2.5                       | 0.35               | 1.74           | 0.96               | 11.4 |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 4549250122477 |
| Diámetro interior | 110 mm        |
| Diámetro interior | 4.331" inch   |
| Diámetro exterior | 240 mm        |
| Diámetro exterior | 9.449" inch   |
| Espesor           | 54.5 mm       |
| Espesor           | 2.146" inch   |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE