

Rodamiento conico 32322-JTEKT - 32322-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32322-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
110	240	84.5	80	65	607	797	1 600	2 200	32322	

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	57.3	128	137	226	198	222	9	19.5	3	2.5	0.35	1.73	0.95	16.6

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250125324
Diámetro interior	110 mm
Diámetro interior	4.331" inch
Diámetro exterior	240 mm
Diámetro exterior	9.449" inch
Espesor	84.5 mm
Espesor	3.327" inch
Peso	10270 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE