

Rodamiento conico 30224-JR-JTEKT - 30224-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30224-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo

Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No.
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> (mm)	<i>r</i> ₁ (mm)	<i>C</i> _r	<i>C</i> _{0r}	Grease lub.	Oil lub.	
120	215	43.5	40	34	3	2.5	347	473	1 700	2 300	30224JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) <i>a</i>	Mounting dimensions (mm)										Constant <i>e</i>	Axial load factors		(Refer. 1) Mass (kg)
		<i>d</i> _a min.	<i>d</i> _b max.	<i>D</i> _a max.	<i>D</i> _b min.	<i>S</i> _a min.	<i>S</i> _b min.	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₀			
4FB	44.2	134	140	203	187	203	6	9.5	2.5	2	0.44	1.38	0.76	6.36	

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250121548
Diámetro interior	120 mm
Diámetro exterior	215 mm
Espesor	43.5 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE