

Rodamiento conico 32972-JR-JTEKT - 32972-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32972-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|----------------------|--------------------------|------------|-------------------------|------------|------------|-------------|--------------------------------------|------------|---------------------------|--------------------|-------|----------------------|------|
| d | D | T | B | C | C_r | C_{0r} | Grease lub. | Oil lub. | | | | | | |
| 360 | 480 | 76 | 76 | 57 | 1 080 | 2 400 | 560 | 740 | 32972JR | | | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d_a min. | d_a max. | D_a min. | D_a max. | S_a min. | S_a max. | r_a min. | r_a max. | | Y_1 | Y_0 | | |
| 4FD | 96.2 | 378 | 379 | 466 | 438 | 466 | 12 | 19 | 3 | 2.5 | 0.46 | 1.31 | 0.72 | 37.1 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952412122 |
| Diámetro interior | 360 mm |
| Diámetro exterior | 480 mm |
| Espesor | 76 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE