

Rodamiento conico 32930-JR-JTEKT - 32930-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32930-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
150	210	38	38	30	286	536	1 600	2 100	32930JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _a min.	d _a max.	D _a min.	D _a max.	S _a min.	S _a max.	r _a min.	r _a max.		Y ₁	Y ₀		
20C	36.1	162	163	200	194	202	7	8	2	2	0.33	1.83	1.01	3.96

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250125706
Diámetro interior	150 mm
Diámetro exterior	210 mm
Espesor	38 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE