

## Rodamiento conico 30330-D-JTEKT - 30330-D-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30330-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
150	320	72	65	46	616	750	970	1400	303300					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>a</sub> min.	d <sub>a</sub> max.	D <sub>a</sub> min.	D <sub>a</sub> max.	S <sub>a</sub> min.	S <sub>a</sub> max.	r <sub>a</sub> min.	r <sub>a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	96.0	172	183	302	270	301	9	26	4	3	0.81	0.74	0.41	23.9

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250122521
Diámetro interior	150 mm
Diámetro interior	5.906" inch
Diámetro exterior	320 mm
Diámetro exterior	12.598" inch
Espesor	72 mm
Espesor	2.835" inch
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE