

Rodamiento conico 30232-JR-JTEKT - 30232-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30232-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo

Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No.
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.	
160	290	52	48	40	542	750	1 200	1 600	30232JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _a min.	d _a max.	D _a min.	D _a max.	S _a min.	S _a max.	r _a min.	r _a max.	r _a max.	r _a max.		Y ₁	Y ₀	
4GB	56.3	178	189	276	252	269	8	12	3	2.5	0.44	1.38	0.76	14.1	

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952421247
Diámetro interior	160 mm
Diámetro exterior	290 mm
Espesor	52 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE