

Rodamiento conico 30238-JR-JTEKT - 30238-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/30238-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo

Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No.
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> (mm)	<i>r</i> ₁ (mm)	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.	
190	340	60	55	46	5	4	729	1030	1 000	1 300	30238JR

Dimension series to ISO355 (Refer.)	Load center (mm) <i>a</i>	Mounting dimensions (mm)										Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)
		<i>d</i> _a min.	<i>d</i> _a max.	<i>D</i> _a min.	<i>D</i> _a max.	<i>S</i> _a min.	<i>S</i> _a max.	<i>r</i> _a min.	<i>r</i> _a max.	<i>r</i> ₀ max.	<i>r</i> ₁ max.		<i>Y</i> ₁	<i>Y</i> ₀	
4GB	66.4	212	225	322	298	318	12	13	4	3	0.44	1.38	0.76	21.9	

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952421520
Diámetro interior	190 mm
Diámetro exterior	340 mm
Espesor	60 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE