

Rodamiento conico 32238-JR-JTEKT - 32238-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32238-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.					
190	340	97	92	75	5	4	1 090	1 740	1 000	1 300	32238JR				
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		r _{2a} min.	r _{2a} max.	
4GD	81.9	212	216	322	286	323	12	22	4	3	0.44	1.38	0.76	36.6	

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952421537
Diámetro interior	190 mm
Diámetro exterior	340 mm
Espesor	97 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE