

Rodamiento conico 32240-JR-JTEKT - 32240-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32240-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|-----|----|----|-------------------------|-----------------|-----------------|-----------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C _{0r} | C _{0r} | Grease lub. | Oil lub. | |
| 200 | 360 | 104 | 98 | 82 | 5 | 4 | 1240 | 1880 | 960 | 1300 | 32240JR |

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
|--|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------------|------|
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 3GD | 84.6 | 222 | 225 | 342 | 302 | 340 | 11 | 22 | 4 | 3 | 0.41 | 1.48 | 0.81 | 44.2 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 4549250124877 |
| Diámetro interior | 200 mm |
| Diámetro exterior | 360 mm |
| Espesor | 104 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE