

Rodamiento conico 32048-JR-JTEKT - 32048-JR-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32048-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
240	360	76	76	57	924	1720	870	1200	32048JR					
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁
4FD	78.5	258	261	346	318	346	12	19	3	2.5	0.46	1.31	0.72	26.8

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	4549250123795
Diámetro interior	240 mm
Diámetro exterior	360 mm
Espesor	76 mm
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE