

## Rodamiento conico 07100-07196-JTEKT - 07100-07196-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/07100-07196-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
25.400	50.005	13.495	14.280	9.525	1.0	1.0	26.7	28.8	7 900	11 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
07100	07196	10.8	30.5	29.5	44.5	47.0	1.0	1.0	0.40	1.49	0.82	0.084	0.035

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952425610
Diámetro interior	25.4 mm
Diámetro exterior	50.005 mm
Espesor	13.495 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE