

## Rodamiento conico 19150R-19283-JTEKT - 19150R-19283-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/19150r-19283-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
38.100	71.996	17.018	16.520	14.283	1.6	1.6	46.1	53.8	5 700	7 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	e	$Y_1$	$Y_2$	Inner ring	Outer ring
19150R	19283	15.7	45.0	43.0	63.0	66.0	1.6	1.6	0.44	1.35	0.74	0.167	0.132

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952426587
Diámetro interior	38.1 mm
Diámetro exterior	71.996 mm
Espesor	17.018 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE