


Rodamiento conico 5578R-5535-JTEKT - 5578R-5535-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/5578r-5535-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	$r_{1\max}$	$r_{2\max}$	C_r	C_{10}	Grease lub.	Oil lub.
53.975	122.238	43.658	43.764	30.512	3.6	3.2	221	318	3 200	4 300

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		d_s	d_b	D_s	D_b	$r_{s\max}$	$r_{b\max}$		Y_1	Y_2	Inner ring	Outer ring
5578R	5535	31.1	73.0	67.0	106.0	116.0	3.6	3.2	0.36	1.67	0.92	1.84	0.807

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952427935
Diámetro interior	53.975 mm
Diámetro exterior	122.238 mm
Espesor	43.658 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE