


Rodamiento conico 685-672-JTEKT - 685-672-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/685-672-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	$r_{1\text{ max}}$	$r_{1\text{ min}}$	C_r	C_{10}	Grease lub.	Oil lub.
98.425	168.275	41.275	41.275	30.162	3.6	3.2	224	349	2 200	3 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_s	d_b	D_s	D_b	$r_{s\text{ max}}$	$r_{b\text{ max}}$	e	Y_1	Y_2	Inner ring	Outer ring
685	672	38.6	116.0	109.0	149.0	160.0	3.6	3.2	0.47	1.28	0.70	2.29	1.22

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952429878
Diámetro interior	98.425 mm
Diámetro exterior	168.275 mm
Espesor	41.275 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE