

## Rodamiento conico L521949R-L521910-JTEKT - L521949R-L521910-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/l521949r-l521910-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |          |          |          |          |                               |                               | Basic load ratings (kN) |                        | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> <sub>a</sub><br>max. | <i>r</i> <sub>b</sub><br>max. | <i>C</i> <sub>r</sub>   | <i>C</i> <sub>10</sub> | Grease lub.                          | Oil lub. |
| 107.950                  | 146.050  | 21.432   | 21.432   | 106.670  | 1.6                           | 1.6                           | 86.4                    | 187                    | 2 300                                | 3 100    |

  

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                       |                       |                       |                               |                               | Constant | Axial load factors    |                       | (Refer.) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d</i> <sub>a</sub>    | <i>d</i> <sub>b</sub> | <i>D</i> <sub>a</sub> | <i>D</i> <sub>b</sub> | <i>r</i> <sub>a</sub><br>max. | <i>r</i> <sub>b</sub><br>max. | <i>e</i> | <i>Y</i> <sub>1</sub> | <i>Y</i> <sub>2</sub> | Inner ring         | Outer ring |
| L521949R    | L521910    | 26.2             | 116.0                    | 114.0                 | 136.0                 | 141.0                 | 1.6                           | 1.6                           | 0.39     | 1.53                  | 0.84                  | 0.665              | 0.325      |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| N° Ean13          | 3663952430065 |
| Diámetro interior | 107.95 mm     |
| Diámetro exterior | 146.05 mm     |
| Espesor           | 21.432 mm     |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE