

Rodamiento de agujas BHTM810-JTEKT - BHTM810-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm810-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type		
								With open ends	With closed end
8	15	10	8.4	4.00	3.30	34 000	BHTM810		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	7.991	8.000	14.977	14.995	6.5	7.3

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952469348
Diámetro interior	8 mm
Diámetro exterior	15 mm
Espesor	10 mm
Peso	6.5 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE