

Rodamiento de agujas BHTM1020-JTEKT - BHTM1020-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm1020-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_r	C_{0r}	Oil lub.	Caged type With open ends With closed end
10	17	20	17.3	10.7	12.5	30 000	BHTM1020

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	9.991	10.000	16.977	16.995	16	18

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952469621
Diámetro interior	10 mm
Diámetro exterior	17 mm
Espesor	20 mm
Peso	16 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE