

Rodamiento de agujas BTM141912A-JTEKT - BTM141912A-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/btm141912a-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C ₀	C _{0r}	Oil lub.	Caged type	With closed end
13.50	19	12	—	6.25	7.95	25 000	With open ends	BTM141912A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	Shaft dia. (H6) max.	Housing bore dia. (H7) min.	Housing bore dia. (H7) max.	With open ends	With closed end
—	—	13.447 ³⁾	13.460 ³⁾	19.000 ⁴⁾	19.021 ⁴⁾	9.5	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952469874
Diámetro interior	13.5 mm
Diámetro exterior	19 mm
Espesor	12 mm
Peso	9.5 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE