


## Rodamiento de agujas BHTM1416-JTEKT - BHTM1416-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm1416-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_{10}$	$C_{90}$	Oil lub.	Caged type		
						With open ends		With closed end	
14	22	16	13.3	11.1	12.6	23 000	<b>BHTM1416</b>		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	13.989	14.000	21.972	21.993	19	21

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470016
Diámetro interior	14 mm
Diámetro exterior	22 mm
Espesor	16 mm
Peso	19 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE