

## Rodamiento de agujas BHTM1420-JTEKT - BHTM1420-JTEKT

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm1420-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>10</sub>	C <sub>90</sub>	Oil lub.	Caged type		
								With open ends	With closed end
14	22	20	17.3	14.4	17.5	23 000	<b>BHTM1420</b>		

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	13.989	14.000	21.972	21.993	23	26

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470030
Diámetro interior	14 mm
Diámetro interior	0.551" inch
Diámetro exterior	22 mm
Diámetro exterior	0.866" inch
Espesor	20 mm
Espesor	0.787" inch
Peso	23 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE